

**OF43A-FA****43”****FHD 2000nits Outdoor Digital Signage**

## Key Feature

- 2000nits
- FHD Resolution
- Android / Monitor (Optional)
- IP65
- Tempered Glass
- Fan Cooling

# Specification

## Display

|                                 |                        |
|---------------------------------|------------------------|
| <b>Model</b>                    | OF43A-FA               |
| <b>Screen Size (Diagonal)</b>   | 43 inch                |
| <b>Native Resolution</b>        | 1080 × 1920            |
| <b>Aspect Ratio</b>             | 9:16                   |
| <b>Brightness</b>               | 2000 cd/m <sup>2</sup> |
| <b>Contrast</b>                 | 1200:1                 |
| <b>View Angle</b>               | 178°(H) / 178°(V)      |
| <b>Color Gamut</b>              | 72%                    |
| <b>Life Time (Light Source)</b> | 50,000 Hrs             |

## Internal Player

|                         |                      |
|-------------------------|----------------------|
| <b>O/S</b>              | Android 7.1          |
| <b>CPU</b>              | ARM Quad-Core RK3288 |
| <b>RAM/ROM</b>          | DDR3 2G / 8G         |
| <b>Input</b>            | HDMI × 1 / USB × 2   |
| <b>Output</b>           | -                    |
| <b>External Control</b> | -                    |
| <b>Networks</b>         | LAN × 1 / WiFi       |
| <b>Built-In Speaker</b> | 5W × 2 (8Ω)          |

## Power

|                             |                     |
|-----------------------------|---------------------|
| <b>Power supply</b>         | AC 100~240V 50/60Hz |
| <b>Power consumption</b>    | ≤ 250W              |
| <b>Rated current</b>        | ≤1.5A               |
| <b>Grounding resistance</b> | ≤0.1Ω               |

## Environment

|                                |                                                                                                                       |
|--------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| <b>Cooling system</b>          | Fan (Heater for under -10°C)                                                                                          |
| <b>Operation temperature</b>   | -25°C~45°C                                                                                                            |
| <b>Storage temperature(°C)</b> | -20°C~60°C                                                                                                            |
| <b>Water and dust proof</b>    | IP65                                                                                                                  |
| <b>Safety Protection</b>       | Leakage Protection, Overload Protection, Overvoltage Protection,<br>Lightning Protection, Over temperature Protection |
| <b>Operation humidity</b>      | 10%~95% RH                                                                                                            |

# Specification

## Physical

|                             |                                         |
|-----------------------------|-----------------------------------------|
| Screen Protection           | 6mm Armored glass (Single Side AR Film) |
| Body Dimension (w/o Stand)  | 2050 (H) × 710 (W) × 180 (D) mm         |
| Body Dimension (with Stand) | 2050 (H) × 710 (W) × 350 (D) mm         |
| Set Weight (with Stand)     | 120 Kg                                  |
| Package Dimension           | TBD                                     |
| Package Weight              | TBD                                     |
| Door open-ward              | Front open                              |

## Dimension Drawing

