



SAMSUNG SMART SIGNAGE DCJ SERIES

Amplify Business Messaging Resonance through Reliable and Efficient Digital Displays

HIGHLIGHTS

- Improve retail and business communications through high-quality professional-grade displays
- Elevate content presentation through FHD picture quality and 300nit brightness
- Engage key audiences over long durations with continuous 16/7 performance
- Integrate new content directly from connected USB drives
- Deliver impactful content at reduced total cost of operation (TCO)

INDUSTRY TRENDS

For both businesses and retailers, clear and effective communications are critical for continued long-term success. To meet these demands, many are turning to innovative digital displays to boost engagement and reinforce branding. As businesses and retailers evaluate digital signage upgrades, they seek solutions that accommodate their core needs. They want displays that are versatile and can scale to meet growth or potential operational changes. They want solutions that are easy to implement and maintain, and do not deter time or resources from day-to-day essentials. And they want to improve their communications without incurring significant costs. Regardless of the environment, businesses and retailers recognize the value of customizable signage to connect with clients, staff, customers or visitors.

WHY SAMSUNG DCJ SERIES?

Samsung's DCJ Series displays combine superior content presentation with reliability, offering business a versatile, cost-effective format to boost engagement and relay timely information. The displays relay audience-ready content with impressive FHD picture quality and continuous 300nit brightness, while also supporting the operational demands of various business environments through 16/7 performance. Each DCJ Series display also offers a multitude of embedded ports that extend connectivity for seamless content sharing, all while maintaining a sleek and stylish design that makes for a welcome addition to any environment.



KEY FEATURES



LOAD AND SHARE CONTENT WITH EASE

Each DCJ Series display leverages the integrated MagicInfo Lite Player to bring a range of on-demand or pre-scheduled images and videos to life. Users can load new content either by connecting their personal laptop directly to the display's built-in port or transferring from a compatible USB drive. For advanced USB convenience, the DCJ Series allows users to store content in a specific folder that will play conveniently without the need for separate scheduling.



CONTROL DISPLAY IN MULTIPLE LOCATIONS INSTANTLY

MagicInfo Lite solution that comes with the embedded media player extends the remote content management over network through MagicInfo server. Media contents of the USB memory stick plugged into the back of the DCJ Series displays can be scheduled to play from a remote PC.

The connection to MagicInfo server also allows remote monitoring and management of the DCJ Series displays. Device information, content playback schedules, network data monitoring, time scheduling, alarms and various controls are all available remotely even without being in front of the displays.



DIVERSIFY CONNECTIVITY PREFERENCES

The DCJ Series displays' versatile interface includes an array of the most widely-used source inputs – including USB, DVI, HDMI1 and HDMI2 ports – that further allow users to customize operations to fit their unique signage network demands. As a result, users can quickly connect their personal devices to the display regardless of the configuration. The DCJ Series displays also feature RJ45 and RS232C ports for broader remote management, and accommodates Set Back Box (SBB) players for diversified high-quality content delivery.

SPECIFICATIONS

MODEL		DC43J	DC49J	
Panel	Diagonal Size	43	49	
	Type	60Hz D-LED BLU	60Hz D-LED BLU	
	Resolution	1920x1080 (16:9)	1920x1080 (16:9)	
	Pixel Pitch(mm)	0.16333(H) x 0.49005(V)	0.18642(H) x 0.55926(V)	
	Active Display Area(mm)	940.89(H) x 529.25(V)	1073.78(H) x 604.00(V)	
	Brightness(Typ.)	300nit	300nit	
	Contrast Ratio(Typ.)	3000:1	3000:1	
	Viewing Angle(H/V)	178:178	178:178	
	Response Time(G-to-G)	8ms	8ms	
	Display Colors	16.7 M	16.7 M	
	Color Gamut	72%	72%	
Operation Hour	16/7	16/7		
Haze	2%	2%		
Display	Dynamic C/R	MEGA	MEGA	
	H-Scanning Frequency	30 ~ 81kHz	30 ~ 81kHz	
	V-Scanning Frequency	48 ~ 75Hz	48 ~ 75Hz	
	Maximum Pixel Frequency	148.5MHz	148.5MHz	
Sound	Speaker Type	Built in Speaker(10W + 10W)	Built in Speaker(10W + 10W)	
Connectivity	INPUT	RGB	DVI-I	DVI-I
		VIDEO	HDMI 1.4 (2), Component(CVBS Common)	HDMI 1.4 (2), Component(CVBS Common)
		HDCP	HDCP1.4	HDCP1.4
		AUDIO	Stereo Mini Jack, RGB/DVI/HDMI/CVBS/Component Audio(Common)	Stereo Mini Jack, RGB/DVI/HDMI/CVBS/Component Audio(Common)
		USB	USB 2.0 x 1	USB 2.0 x 1
	OUTPUT	RGB	N/A	N/A
		VIDEO	N/A	N/A
		AUDIO	Stereo Mini Jack	Stereo Mini Jack
		Power Out	N/A	N/A
		USB	N/A	N/A
	EXTERNAL CONTROL		RS232C(in) thru stereo jack, RJ45	RS232C(in) thru stereo jack, RJ45
EXTERNAL SENSOR		IR	IR	
Tuner		Yes (only for NA/KR)	Yes (only for NA/KR)	
Type		Internal	Internal	
Power Supply		AC 100 - 240 V- (+/- 10 %), 50/60 Hz	AC 100 - 240 V- (+/- 10 %), 50/60 Hz	
Power	Power Consumption	Max[W/h]	99	121
		Typical[W/h]	(W/W)53, (US)38, (KR)62	(W/W)57, (US)42, (KR)76
	BTU(Max)	337	412.6	
	Sleep mode	less than 0.5W	less than 0.5W	
	Off mode	0	0	
Mechanical Spec	Dimension (mm)	Set	985.5 X 574.8 X 73.4	1118.8 X 650.0 X 74.2
		Package	1099 X 672 X 156	1236 X 750 X 161
	Weight (kg)	Set	7.8	10.1
		Package	11.5	14.7
	VESA Mount		200*200mm	200*200mm
	Protection Glass		N/A	N/A
	Stand Type		N/A	N/A
Bezel Width (mm)		17.3(Top), 18.3(Bottom), 21.3(Side)	17.4(Top), 18.5(Bottom), 21.5(Side)	
Operation	Operating Temperature	0°C- 40°C	0°C- 40°C	
	Humidity	10-80%	10-80%	
Feature	Key	Slim & Light LFD with Built-in MagicInfo Lite		
	Special	H/W	Super Clear Coating, Temperature Sensor, Pivot Display, Button Lock, Clock Battery (168hrs Clock Keeping), Built in Speaker (10W x 2)	
		S/W	Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play (DDC2B), Built-In MagicInfo Lite, Firmware Update by Network	
	Internal Player (Embedded H/W)	Processor	MIPS 24K	MIPS 24K
		On-Chip Cache Memory	L1 : 16KB/16KB L2 : 128KB	L1 : 16KB/16KB L2 : 128KB
		Clock Speed	650MHz	650MHz
		Main Memory Interface	512MB	512MB
		Graphics	N/A	N/A
		Storage (FDM)	179MB	179MB
		Multimedia	N/A	N/A
		IO Ports	N/A	N/A
Operating System	Samsung Proprietary OS(VDLinux)			
Accessories	Included	Quick Setup Guide, Regulatory Guide, Warranty Card, Power Cord, Remote Controller, Batteries, RS232C(IN) adapter, ANT Shield Box(Only for KR)		
	Optional	Stand	STN-L3240E	STN-L3240E
		Mount	WMN4070SE	WMN4070SE
		Media Player	SBB (Not attachable)	SBB (Not attachable)

About Samsung Electronics Co., Ltd.

Samsung inspires the world and shapes the future with transformative ideas and technologies. The company is redefining the worlds of TVs, smartphones, wearable devices, tablets, digital appliances, network systems, and memory, system LSI, foundry and LED solutions. For the latest news, please visit the Samsung Newsroom at <http://news.samsung.com>.

SMART Signage

For more information about Samsung SMART Signage DCJ Series Displays, visit www.samsung.com/business or www.samsung.com/displaysolutions

Copyright © 2017 Samsung Electronics Co. Ltd. All rights reserved. Samsung is a registered trademark of Samsung Electronics Co. Ltd. Specifications and designs are subject to change without notice. Non-metric weights and measurements are approximate. All data were deemed correct at time of creation. Samsung is not liable for errors or omissions. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognized and acknowledged.

Samsung Electronics Co., Ltd.
416, Maetan 3-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do 443-772, Korea

2017-11

SAMSUNG